





Unspoil your view with this frameless folding door solution.



A lot of homes have their beautiful views spoiled by aluminium uprights. Our Neo-Fold system is specifically designed to get rid of those "view-spoiling" uprights. It is designed to fit in the outer frame and tracks of most existing framed folding doors.

ADVANCED FEATURES

- No uprights to spoil your views.
- Dry-fit clamp sections for easy installation and onsite adjustments.
- Available in 8 or 10mm toughened safety glass.
- Upgrade from framed to frameless
- using existing tracks from most | 100% Manufactured in framed stack doors.
- Standard installation method.
- Can be used as access door.
- Low maintenance.
- Bottom running, this improves installation process.
- South Africa.
- Unique panel retaining system.
- Non-corrosive materials
- Double-lip weather seals.

SECURITY

- Anti-lift feature.
- Lock with key on both sides (thumb-lock option in inside available).
- Stainless steel locking-pins top and bottom.
- 8 or 10mm Toughened safety glass are 200% stronger than normal 4mm sliding doors - 6.38mm in framed stack doors.

TECHNICAL DATA

- 75kg Per panel (this equals to a 3 x 1m panel with 10mm glass).
- Max height 2400mm.
- Max panel width 900mm
- Available in all standard aluminium colours (white, bronze or matt charcoal).
- Non-standard colours on special request.
- Hardware in white, bronze, matt charcoal, black or natural.

SUPREME WEATHER SEALING

MORE UNIQUE FACTS:

- Easiest opening action ever.
- Double-lip seals throughout the system running full height.
- Extra bubble seal on the inside.
- UV stable weather seals that will not go yellow in sun.
- Can be installed in tracks of most existing framed folding doors without replacing the outer frame. This means no chopping into plaster resulting in a dust free installation.

NeoFold by Inovision Distrobutors - www.inovision.biz